

MAJOR Slurry Handling Equipment

The Major range of slurry handling equipment covers a variety of conditions for farmers and contractors. Tankers in each category are designed and built around a specific use or requirement. Buyers can further customise the vacuum tankers with an extensive list of industry-leading components and accessories.

Unique design features of all MAJOR tankers:

- ✓ Barrels are supported by separate, heavier chassis which carries 80% of the load to bear the stress of pulling heavy loads and at longer distances.
- ✓ Barrels are made of 6mm thick steel for maximum strength



Class	Standard	Contractor	Alpine	Tandem
Capacity	1150–2000 gallon	2050–3100 gallon	2150, 2300, 2670 gallon	2000–4000 gallon
Key design specification	Choice of Agri and LGP models	Recessed wheels (28"–30" wheels) for increased stability	Lower centre of gravity (by 14")	Hi-speed commercial axles rated to 100km/hr
	Detachable parking stand	Heavy duty commercial axles	Larger wheel recess for greater stability on hills and high road speeds	Heavy duty bogey steering axles
	PTO holder	Internal baffling to prevent wave motions	Internal baffling to prevent wave motions	Internal baffling to prevent wave motions
	Fully galvanised	Side and rear lights	Side and rear lights	Shearbolt PTO on shaft



All tankers include the following road safety standards:

- Safety breakaway cable for safer use on public roads
- Hydraulic brakes in compliance with regulations
- Rubber buffers on drawbar for easier towing and smoother journeys

Best for



<ul style="list-style-type: none"> ✓ Small holdings ✓ Water bowser ✓ Dust suppressor 	<ul style="list-style-type: none"> ✓ Large farmers with multiple sites ✓ Contractors 	<ul style="list-style-type: none"> ✓ Larger farmers with multiple sites ✓ Contractors working in hillier and wetter ground 	<ul style="list-style-type: none"> ✓ Transportation and application of digestate from AD plants ✓ Large dairy operations ✓ Zero-grazing operations
---	--	--	---