Muckspreaders



- Reinforced 4mm body welded inside and out.
- Reinforced 6mm end plates
- Reinforced drawbar for absolute rigidity when in operation.
- 8 cu. m. capacity (9.5 cubic yd.)
- 8 ton 8 stud 80mm square bolt on axle to reinforced body support for safe working operation with 550 x 60 x 22.5 as standard wheels
- Secure simple galvanised clip on galvanised chain guard for easy access for maintenance
- Heavy duty balanced rotor with 12mm discharge chains and spreader plates.

 Heavy duty 4 bolt flange bearings mounted away from the body for low maintenance.

- Large wash-out bung
- PTO speed 540RPM
- Pick up eye, shoe rest and PTO rest as standard.
- Double starter bars for quick start up.
- Heavy duty 1" (25mm)
 Duplex drive chain
- Heavy duty galvanised hyd opening reinforced lid
- Reinforced loading edge

Model	MS 1000
Cubic Yard Capacity	9.5
Power Req.	100hp
Door	Hydraulic
Chain / Flails	36 no x 13mm
Drum Thickness	4mm
Overall Length	5.6m
Width	2.5m
Loading Height	1.67m
Lights	Standard
Brakes	Standard
Unladen Weight	1800kgs
PTO Speed	540rpm
Dia of Drum	150cm
Length of Drum	370cm
Wheel Sizes Standard	550 x 60 x 22.5
Wheel Sizes Optional	P.O.A